

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 12/16/2022 Revision date: 12/16/2022

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Dolomitic Limestone

Product type : Solid

Other means of identification : Dolostone, Dolomite, Dolomitic Limestone.

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Desulphurisation

Neutralisation Aggregates

Mineral filler and pigment.

Flux agent Liming material

1.3. Supplier

Manufacturer

GRAYMONT

#200-10991 Shellbridge Way Richmond, BC V6X 3C6 - Canada

T 1 604 207-4292; Toll free1 866 207-4292 - F 1 604 207-9014

www.graymont.com

Distributor

Graymont Western US Inc 585 W Southridge Way

Sandy, Utah 84070 - United States

T +1 801-262-3942

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Carcinogenicity, Category 1A

Specific target organ toxicity - Repeated exposure, Category 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger

Hazard statements (GHS) : May cause cancer (inhalation).

Causes damage to organs (lungs) through prolonged or repeated exposure.

Precautionary statements (GHS) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling.

12/16/2022 EN (English) Page 1

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Calcium carbonate	Calcium carbonate C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1	50 – 75
Carbonic acid, magnesium salt (1:1)	Carbonic acid, magnesium salt (1:1) Magnesium carbonate / C.I. 77713 / Carbonate, magnesium / CI 77713 / MAGNESIUM CARBONATE / magnesite / Magnesite	CAS-No.: 546-93-0	50 – 75
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alphaQuartz / Silica, crystalline, .alphaquartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystallinealpha.quartz / Silica, .alphaquartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.1 – 1

Comments

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

12/16/2022 EN (English) 2/11

[:] Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation

persists.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious

person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Chronic symptoms : May cause cancer. Causes damage to organs through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Metal oxides.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

12/16/2022 EN (English) 3/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Methods for cleaning up

: Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. . Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Obtain special instructions before use. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Do not breathe gas, fumes, vapour or spray. Avoid generating dust. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Good housekeeping is important to prevent accumulation of dust. Wear appropriate PPE (see

Hygiene measures

Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a wellventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters		
Dolomitic Limestone		
No additional information available		
Calcium carbonate (471-34-1)	Calcium carbonate (471-34-1)	
Canada (Alberta) - Occupational Exposure Lim	nits	
OEL TWA	10 mg/m³	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWA)	10 mg/m³ (total dust)	
Canada (Saskatchewan) - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (Limestone)	
OEL STEL	20 mg/m³ (Limestone)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
Carbonic acid, magnesium salt (1:1) (546-93-0)		
Canada (British Columbia) - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (total dust (Magnesite) 3 mg/m³ (respirable fraction (Magnesite)	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWA)	10 mg/m³ (containing no Asbestos and <1% Crystalline silica-total dust (Magnesite)	

12/16/2022 EN (English) 4/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Carbonic acid, magnesium salt (1:1) (546-93-0) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA OEL STEL 20 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 10 mg/m³ (respirable dust (Magnesite) Smg/m³ (respirable dust (Magnesite) Smg/m³ (respirable dust (Magnesite) Smg/m³ (respirable dust (Magnesite) Smg/m³ (respirable dust (Magnesite) Canada (Alberta) - Occupational Exposure Limits OEL TWA 0.025 mg/m³ (respirable particulate) Notations and remarks Carcinogenicity A2 Regulatory reference Alberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quantz OEL TWA 0.025 mg/m² (respirable) Notations and remarks ACGIL Acrainogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5. Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Ouebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Guebec) - Occupational Exposure Limits USA - ACGIH - Occupational Exposure Limits USA - ACGIH - Occupational Exposure Limits USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quantz ACGIH OEL TWA 0.025 mg/m³ (respirable dust) Canada (Guebec) - Occupational Exposure Limits Local name Silica crystaline - quantz ACGIH - Occupational Exposure Limits Local name Outs Crotal Dusty (Silica Crystalline) Suspected Human Carcinogen ACGIH - Carcinogen ACGIH - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits Suspected Human Carcinogen ACGIH - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits Suspected Human Carcinogen ACGIH - Occupational Exposure Limits USA - OSHA - Occupat		5.1200) Huzootti 2012 and the Huzurdous Hodden Regulations (HER) White 2010	
OEL STEL USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 10 mg/m² (total dust (Magnesite) 5 mg/m² (respirable dust (Magnesite) 6 mg/m² (respirable dust (Magnesite) 7 Canada (Alberta) - Occupational Exposure Limits 10 cari arame 10 carada (Alberta) - Occupational Exposure Limits 10 canada (Alberta) - Occupational Exposure Limits 10 canada (Alberta) - Occupational Exposure Limits 10 canada (British Columbia) - Occupational Exposure Limits 11 canada (British Columbia) - Occupational Exposure Limits 12 canada (British Columbia) - Occupational Exposure Limits 13 canada (British Columbia) - Occupational Exposure Limits 14 canada (British Columbia) - Occupational Exposure Limits 15 canada (Ordario) - Occupational Exposure Limits 16 canada (Ordario) - Occupational Exposure Limits 17 canada (Ordario) - Occupational Exposure Limits 18 canada (Ordario) - Occupational Exposure Limits 19 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 Canada (Saskatchewan) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 10 CEL TWA 10 canada (Ordario) - Occupational Exposure Limits 11 canada (Ordario) - Occupational Exposure Limits 12 canada (Ordario) - Occupational Exposure Limits 13 canada (Ordario) - Occupational Exposure Limits 14 canada (Ordario) - Occupational Exposure Limits 15 canada (Ordario) - Occupational Exposure Limits 16 canada (Ordario) - Occupational Exposure Limits 17 canada (Ordario) - Occupational Exposure Limits 18 canada (Ordario) - Occupational Exposure Limits 19 canada (Ordario) - Occupational Exposure Limits 10 canada (Ordario) - Occupational Exposure Lim	Carbonic acid, magnesium salt (1:1) (546-93-0		
OEL STEL 20 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 10 mg/m³ (total dust (Magnesite) 5 mg/m² (respirable particulate) OEL TWA 0.025 mg/m² (respirable particulate) Notations and remarks Caroinogenicity A2 Regulatory reference Alberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits Local name Silca, Crystalline - alpha quartz OEL TWA 0.025 mg/m² (respirable) Notations and remarks ACGIH - Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSate BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m² (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits OEL TWA 0.1 mg/m² (respirable dust) Canada (Guebec) - Occupational Exposure Limits OEL TWA 0.5 mg/m² (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits OEL TWA 0.05 mg/m² (respirable particulate matter) Remark (ACGIH) TUVA 0.05 mg/m² (respirable particulate matter) Remark (ACGIH) TUVA 0.025 mg/m² (respirable particulate matter) Remark (ACGIH) TUVA 0.025 mg/m² (respirable particulate matter) Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Ouartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA 11 50 μg/m² (Respirable cystalline silica) Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Canada (Saskatchewan) - Occupational Exposure L	imits	
USA - NIOSH - Occupational Exposure Limits 10 mg/m³ (respirable dust (Magnesite) 5 mg/m³ (respirable dust (Magnesite) Canada (Alberta) - Occupational Exposure Limits Local name Silica-Crystalline: Quartz OEL TWA 0.025 mg/m³ (respirable particulate) Notations and remarks Carcinogenicity A2 Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alipha quartz Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alipha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OH.5 Quidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Guebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits UEN A-ACGIH - Occupational Exposure Limits UEN A- ACGIH - Occupational Exposure Limits UEN A- OSHA - Occupational Exposure Limits USA- ACGIH - Occupational Exposure Limits USA- OSHA - Occupational Exposure Limits	OEL TWA	10 mg/m³	
NIOSH REL TWA 10 mg/m² (total dust (Magnesite) 5 mg/m² (respirable dust (Magnesite) Guartz (14808-60-7) Canada (Alberta) - Occupational Exposure Limits Local name Silica-Crystalline: Quartz OEL TWA 0.025 mg/m² (respirable particulate) Notations and remarks Carcinogenicity A2 Regulatory reference Aberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits OEL TWA 0.025 mg/m² (respirable) Notations and remarks Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m² (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m² (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m² (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m² (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits DEL TWA 0.05 mg/m² (respirable particulate matter) Remark (ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH Cel TWA 0.025 mg/m² (respirable particulate matter) Remark (ACGIH) T. T. W® Basis: Pulm fibrosis: lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH Acmical category Suspected Human Carcinogen ACGIH Acmical category Generic ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA {1} 50 μg/m² (Respirable crystalline silica) Remark (OSHA) 7 specific particulate Cystalline silica) CSHA PEL TWA {1} 50 μg/m² (Respirable crystalline silica) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OEL STEL	20 mg/m³	
Canada (Alberta) - Occupational Exposure Limits	USA - NIOSH - Occupational Exposure Limits		
Canada (Alberta) - Occupational Exposure Limits Local name Silica-Crystalline: Quartz OEL TWA 0.025 mg/m³ (respirable particulate) Notations and remarks Carcinogenicity A2 Regulatory reference Acgulatory reference Acgulatory reference Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Cacill chemical category Regulatory reference ACGIH OEL TWA 0.05 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis: lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: «CFR Table Z-1. Regulatory reference (US-OSHA) OSHA - IDLH - Occupational Exposure Limits	NIOSH REL TWA		
Local name Silica-Crystalline: Quartz OEL TWA 0.025 mg/m³ (respirable particulate) Notations and remarks Carcinogenicity A2 Regulatory reference Alberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Cosh A - Occupational Exposure Limits Cosh - Occupational Exposure Limits Cosh - Occupational Exposure Limits Cosh - Occupational Exposure Limits	Quartz (14808-60-7)		
OEL TWA O.025 mg/m³ (respirable particulate) Notations and remarks Carcinogenicity A2 Regulatory reference Alberta Regulation 191/2021 Canada (Britrish Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quartz OEL TWA O.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA O.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) O.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA O.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA O.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA - Occupational Exposure Limits	Canada (Alberta) - Occupational Exposure Limits		
Notations and remarks Carcinogenicity A2 Regulatory reference Alberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] S0 µg/m³ (Respirable crystalline silica) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Local name	Silica-Crystalline: Quartz	
Regulatory reference Alberta Regulation 191/2021 Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline) CSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline) CSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline) OSHA - Occupational Exposure Limits Local name OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OEL TWA	0.025 mg/m³ (respirable particulate)	
Canada (British Columbia) - Occupational Exposure Limits Local name Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Cacli Ca	Notations and remarks	Carcinogenicity A2	
Local name Silica, Crystalline - alpha quartz OEL TWA 0.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Regulatory reference	Alberta Regulation 191/2021	
OEL TWA O.025 mg/m³ (respirable) Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA O.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) O.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA O.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Canada (British Columbia) - Occupational Exposure	e Limits	
Notations and remarks ACGIH Carcinogenicity category A2; IARC group 1 carcinogen Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA 0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SIO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Local name	Silica, Crystalline - alpha quartz	
Regulatory reference OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC) Canada (Ontario) - Occupational Exposure Limits OEL TWA O.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) O.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA O.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA O.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] S0 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OEL TWA	0.025 mg/m³ (respirable)	
Canada (Ontario) - Occupational Exposure Limits OEL TWA O.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) O.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA O.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen	
OEL TWA O.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline) Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) O.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA O.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)	
Canada (Quebec) - Occupational Exposure Limits VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Canada (Ontario) - Occupational Exposure Limits		
VEMP (OEL TWA) 0.1 mg/m³ (respirable dust) Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OEL TWA	0.1 mg/m³ (designated substances regulation-respirable fraction (Silica, crystalline)	
Canada (Saskatchewan) - Occupational Exposure Limits OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] So µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Canada (Quebec) - Occupational Exposure Limits		
OEL TWA 0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	VEMP (OEL TWA)	0.1 mg/m³ (respirable dust)	
USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] S0 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Canada (Saskatchewan) - Occupational Exposure Limits		
Local name Silica crystaline - quartz ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Suspected Human Carcinogen ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OEL TWA	0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed))	
ACGIH OEL TWA 0.025 mg/m³ (respirable particulate matter) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] So µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	USA - ACGIH - Occupational Exposure Limits		
Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] S0 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Local name	Silica crystaline - quartz	
ACGIH chemical category Regulatory reference ACGIH 2022 USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	ACGIH OEL TWA	0.025 mg/m³ (respirable particulate matter)	
Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] So μg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
USA - OSHA - Occupational Exposure Limits Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	ACGIH chemical category	Suspected Human Carcinogen	
Local name Quartz (Total Dust) (Silica: Crystalline) OSHA PEL TWA [1] 50 μg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Regulatory reference	ACGIH 2022	
OSHA PEL TWA [1] S0 µg/m³ (Respirable crystalline silica) Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
Remark (OSHA) Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	Local name	Quartz (Total Dust) (Silica: Crystalline)	
source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts USA - IDLH - Occupational Exposure Limits	OSHA PEL TWA [1]	50 μg/m³ (Respirable crystalline silica)	
USA - IDLH - Occupational Exposure Limits	Remark (OSHA)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts	
IDLH 50 mg/m³ (respirable dust)	USA - IDLH - Occupational Exposure Limits		
	IDLH	50 mg/m³ (respirable dust)	

12/16/2022 EN (English) 5/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Quartz (14808-60-7)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	0.05 mg/m³ (respirable dust)
USA - MSHA - Occupational Exposure Limits	
MSHA PEL TWA 8/40 h	30 mg/m³ / (%SiO2) + 2 mg/m³ (Total dust) 10 mg/m³ / (%SiO2) + 2 mg/m³ (Respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and

safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Physical state

Relative density

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

: Solid

2.75 - 2.99

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Powder. Colour White to grey Odour Odourless Odour threshold No data available рΗ 9 - 9.2 at 25 °C (77 °F) Melting point Not applicable : Not applicable Freezing point Boiling point : Not applicable Flash point : Not applicable Relative evaporation rate (butylacetate=1) : Not applicable Flammability : No data available Vapour pressure : Not applicable Relative vapour density at 20°C / 68 °F : Not applicable

Solubility : Water: 0.03 % at 20 °C (68 °F)

Partition coefficient n-octanol/water : Not applicable
Auto-ignition temperature : Not applicable
Decomposition temperature : 725 °C (1337 °F)

12/16/2022 EN (English) 6/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Viscosity, kinematic : Not applicable
Viscosity, dynamic : No data available
Explosive limits : Not applicable
Explosive properties : No data available
Oxidising properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

alcium carbonate (471-34-1)	
LD50 oral rat	6450 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
ATE CA (oral)	6450 mg/kg bodyweight

Carbonic acid, magnesium salt (1:1) (546-93-0)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420
	(Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity -
	Fixed Dose Procedure)

Skin corrosion/irritation : Not classified.

pH: 9 – 9.2 at 25 °C (77 °F)

12/16/2022 EN (English) 7/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Serious eye damage/irritation : Not classified.

pH: 9 - 9.2 at 25 °C (77 °F)

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : May cause cancer if inhaled. Risk of cancer depends on duration and level of exposure.

<u> </u>
1 - Carcinogenic to humans
Known Human Carcinogens
Yes

Reproductive toxicity : Not classified. STOT-single exposure : Not classified.

STOT-repeated exposure : Causes damage to organs (lungs) through prolonged or repeated exposure.

alcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

Dolomitic Limestone		
	Viscosity, kinematic	Not applicable
	Symptoms/effects after inhalation :	May cause irritation to the respiratory tract.
	Symptoms/effects after skin contact :	May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
	Ourse to see to the standard and a second and	Management of the Company of the Arms of t

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Chronic symptoms : May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

Symptoms/effects after ingestion

12.1. Toxicity

Ecology - general : No known significant effects or critical hazards.

12.2. Persistence and degradability

Dolomitic Limestone	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Dolomitic Limestone	
Partition coefficient n-octanol/water	Not applicable
Bioaccumulative potential	Not established.

12/16/2022 EN (English) 8/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Calcium carbonate (471-34-1)

BCF - Fish [1] (no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations

: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

12/16/2022 EN (English) 9/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations



This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Carbonic acid, magnesium salt (1:1)(546-93-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 12/16/2022 Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



12/16/2022 EN (English) 10/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Carc. 1A	Carcinogenicity, Category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

SDS HazCom 2012 - WHMIS 2015 (Nexreg) - Section 15 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

12/16/2022 EN (English) 11/11