

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Issue date: 2022-10-18 Revision date: 2023-11-20 Version: 1.1

SECTION 1: Identification

Product form: MixtureProduct name: Dolomitic Lime Kiln DustProduct code: Not availableSynonyms: SolidOther means of identification: KEMIDOL Hydrate, Type N; Dolomitic Hydrated Agricultural Lime; SUPER LIMOID S Mason's Lime; MORTASEAL Autoclaved Masons Lime; IVORY Autoclaved Finish Lime; SNOWDRIFT Autoclaved Finish Lime; KEMIDOL Superhydrate; KEMIDOL Superhydrate; ALKA 240; Dolomitic Hydrated Spray Lime; Dolomitic Hydrated Lime, 10# bag; Dolomitic Hydrated Lime, 25# bag; DAP Dolomitic Hydrated Lime; BONDCRETE Mason's & Stucco Lime; SUPER LIMOID SA Mason's & Stucco Lime; GRAND PRIZE Hydrated Finish Lime; RED TOP Finish Lime; WESTERN MIRACLE Lime; WESTERN FINISHING Lime; WESTERN American Masonry; WESTERN LIMATE; WESTERN Mason's	1.1. Identification	
Lime	Product name Product code Synonyms	 Dolomitic Lime Kiln Dust Not available Solid KEMIDOL Hydrate, Type N; Dolomitic Hydrated Agricultural Lime; SUPER LIMOID S Mason's Lime; MORTASEAL Autoclaved Masons Lime; IVORY Autoclaved Finish Lime; SNOWDRIFT Autoclaved Finish Lime; CANADIAN SNOWDRIFT Autoclaved Finish Lime; KEMIDOL Superhydrate; KEMIDOL Superhydrate; ALKA 240; Dolomitic Hydrated Spray Lime; Dolomitic Hydrated Lime, 10# bag; Dolomitic Hydrated Lime, 25# bag; DAP Dolomitic Hydrated Lime; BONDCRETE Mason's & Stucco Lime; SUPER LIMOID SA Mason's & Stucco Lime; GRAND PRIZE Hydrated Finish Lime; RED TOP Finish Lime; WESTERN MIRACLE Lime; WESTERN FINISHING Lime; WESTERN American Masonry; WESTERN LIMATE; WESTERN Mason's

1.2. Recommended use and restrictions on use

Use of the substance/mixture

: Neutralization, stabilization, absorption, dolomitic agricultural liming material.

1.3. Supplier

Manufacturer

GRAYMONT #200-10991 Shellbridge Way Richmond, BC V6X 3C6 - Canada T 1 604 207-4292 - F 1 604 207-9014

1.4. Emergency telephone number

Emergency number

: CHEMTREC, US (800-424-9300), INTERNATIONAL: (703-527-3887)

Sandy, Utah 84070 - United States

Graymont Western US Inc

585 W Southridge Way

T+1 801-262-3942

Distributor

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Carcinogenicity Category 1A Specific target organ toxicity - Single exposure, Category 3 Specific target organ toxicity - Repeated exposure, Category 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS)



Signal word (GHS)

: Danger

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Hazard statements (GHS)	 Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer (Inhalation). Causes damage to organs (lungs) through prolonged or repeated exposure.
Precautionary statements (GHS)	 Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Calcium carbonate	Calcium carbonate C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1	50 – 75
Carbonic acid, magnesium salt (1:1)	Carbonic acid, magnesium salt (1:1) Magnesium carbonate / C.I. 77713 / Carbonate, magnesium / CI 77713 / MAGNESIUM CARBONATE / magnesite / Magnesite	CAS-No.: 546-93-0	50 – 75
Calcium hydroxide	Calcium hydroxide Calcium dihydroxide / Calcium hydroxide (Ca(OH)2) / Hydrated lime / Lime, hydrated / CALCIUM HYDROXIDE / Slaked lime	CAS-No.: 1305-62-0	30 – 60
Magnesium oxide (MgO)	Magnesium oxide (MgO) Calcined magnesite / Magnesium oxide / MAGNESIUM OXIDE / Magnesia	CAS-No.: 1309-48-4	25 – 50

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Calcium oxide	Calcium oxide Lime / Quicklime / CALCIUM OXIDE / Quicklime (CaO) / Calcium oxide (CaO) / Lime (calcium oxide)	CAS-No.: 1305-78-8	0-20
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alphaQuartz / Silica, crystalline, .alphaquartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline- .alpha.quartz / Silica, .alphaquartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.0001 – 1

Comments

: Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and e	ffects (acute and delayed)
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Symptoms may include redness, drying, defatting and cracking of the skin. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishing n	nedia		
	Use extinguishing media appropriate for surrounding fire. Do not use water jet.		
5.2. Specific hazards arising from the chemic	al		
Fire hazard :	Products of combustion may include, and are not limited to: oxides of carbon, irritating vapours.		
5.3. Special protective equipment and precautions for fire-fighters			
Protection during firefighting :	Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).		

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.	
6.1.1. For non-emergency personnel		
No additional information available		
6.1.2. For emergency responders		
No additional information available		
6.2. Environmental precautions		
Prevent entry to sewers and public waters.		
6.3. Methods and material for containment and cleaning up		
For containment	: Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).	
Methods for cleaning up	: Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Provide ventilation. Avoid dust formation.	

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Good housekeeping is important to prevent accumulation of dust. Ensure adequate natural or mechanical ventilation in the form local or general exhaust ventilation is in use to ensure exposure is below established regulatory limits. If ventilation is not adequate, use respiratory protection in the form of a CSA/NIOSH- Approved Particulate Filtering Facepiece Respirators such as an N95 respirator or equivalent. Wash contaminated clothing before reuse. Always wash hands after handling the product.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Calcium carbonate (471-34-1)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	10 mg/m ³ (total dust)	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (Limestone)	
OEL STEL	20 mg/m ³ (Limestone)	
Canada (Northwest Territories) - Occupational Expo	osure Limits	
OEL TWA	10 mg/m ³ (Limestone)	
OEL STEL	20 mg/m ³ (Limestone)	
Canada (Saskatchewan) - Occupational Exposure L	imits	
OEL TWA	10 mg/m ³ (Limestone)	
OEL STEL	20 mg/m ³ (Limestone)	
Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	30 mppcf 10 mg/m ³	
OEL STEL	20 mg/m ³	
Carbonic acid, magnesium salt (1:1) (546-93-0)		
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust (Magnesite)	
Canada (British Columbia) - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (total dust (Magnesite) 3 mg/m³ (respirable fraction (Magnesite)	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (Magnesite)	
OEL STEL	20 mg/m ³ (Magnesite)	
Canada (Northwest Territories) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (Magnesite)	
OEL STEL	20 mg/m ³ (Magnesite)	
Canada (Saskatchewan) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³	

Safety Data Sheet

Carbonic acid, magnesium salt (1:1) (546-93-0)		
OEL STEL	20 mg/m ³	
Calcium oxide (1305-78-8)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	2 mg/m ³	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	2 mg/m ³	
Canada (British Columbia) - Occupational Exposure	e Limits	
OEL TWA	2 mg/m ³	
Canada (Manitoba) - Occupational Exposure Limits		
OEL TWA	2 mg/m ³	
Canada (New Brunswick) - Occupational Exposure	Limits	
OEL TWA	2 mg/m³	
Canada (Newfoundland and Labrador) - Occupation	nal Exposure Limits	
OEL TWA	2 mg/m³	
Canada (Nova Scotia) - Occupational Exposure Lim	its	
OEL TWA	2 mg/m³	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	2 mg/m³	
OEL STEL	4 mg/m ³	
Canada (Northwest Territories) - Occupational Expo	osure Limits	
OEL TWA	2 mg/m ³	
OEL STEL	4 mg/m ³	
Canada (Ontario) - Occupational Exposure Limits		
OEL TWA	2 mg/m ³	
Canada (Prince Edward Island) - Occupational Expo	osure Limits	
OEL TWA	2 mg/m ³	
Canada (Saskatchewan) - Occupational Exposure L	imits	
OEL TWA	2 mg/m ³	
OEL STEL	4 mg/m ³	
Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	2 mg/m ³	
OEL STEL	4 mg/m ³	
USA - ACGIH - Occupational Exposure Limits		
Local name	Calcium oxide	
ACGIH OEL TWA	2 mg/m ³	
Remark (ACGIH)	TLV® Basis: URT irr	
Regulatory reference	ACGIH 2020	
	1	

Safety Data Sheet

Calcium oxide (1305-78-8)		
USA - OSHA - Occupational Exposure Limits		
Local name	Calcium oxide	
OSHA PEL TWA [1]	5 mg/m ³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Magnesium oxide (MgO) (1309-48-4)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (fume)	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	10 mg/m ³ (inhalable dust)	
Canada (British Columbia) - Occupational Exposure	e Limits	
OEL TWA	10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume)	
OEL STEL	10 mg/m³ (respirable dust and fume)	
Canada (Manitoba) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (inhalable particulate matter)	
Canada (New Brunswick) - Occupational Exposure	Limits	
OEL TWA	10 mg/m ³ (inhalable fraction)	
Canada (Newfoundland and Labrador) - Occupation	al Exposure Limits	
OEL TWA	10 mg/m ³ (inhalable particulate matter)	
Canada (Nova Scotia) - Occupational Exposure Lim	its	
OEL TWA	10 mg/m ³ (inhalable particulate matter)	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (inhalable fraction)	
OEL STEL	20 mg/m ³ (inhalable fraction)	
Canada (Northwest Territories) - Occupational Expo	osure Limits	
OEL TWA	10 mg/m ³ (inhalable fraction)	
OEL STEL	20 mg/m³ (inhalable fraction)	
Canada (Ontario) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (inhalable particulate matter)	
Canada (Prince Edward Island) - Occupational Expo	osure Limits	
OEL TWA	10 mg/m ³ (inhalable particulate matter)	
Canada (Saskatchewan) - Occupational Exposure L	imits	
OEL TWA	10 mg/m ³ (inhalable fraction)	
OEL STEL	20 mg/m ³ (inhalable fraction)	
Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³ (fume)	
OEL STEL	10 mg/m³ (fume)	
I	1	

Safety Data Sheet

Magnesium oxide (MgO) (1309-48-4)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	15 mg/m ³ (fume, total particulate)	
Calcium hydroxide (1305-62-0)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	5 mg/m ³	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	5 mg/m³	
Canada (British Columbia) - Occupational Exposure	e Limits	
OEL TWA	5 mg/m³	
Canada (Manitoba) - Occupational Exposure Limits		
OEL TWA	5 mg/m ³	
Canada (New Brunswick) - Occupational Exposure	Limits	
OEL TWA	5 mg/m³	
Canada (Newfoundland and Labrador) - Occupation	al Exposure Limits	
OEL TWA	5 mg/m³	
Canada (Nova Scotia) - Occupational Exposure Lim	its	
OEL TWA	5 mg/m³	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
OEL STEL	10 mg/m ³	
Canada (Northwest Territories) - Occupational Exposure Limits		
OEL TWA	5 mg/m ³	
OEL STEL	10 mg/m ³	
Canada (Ontario) - Occupational Exposure Limits	·	
OEL TWA	5 mg/m³	
Canada (Prince Edward Island) - Occupational Exposure Limits		
OEL TWA	5 mg/m ³	
Canada (Saskatchewan) - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
OEL STEL	10 mg/m ³	
Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	5 mg/m ³	
OEL STEL	10 mg/m ³	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³	
	I	

Safety Data Sheet

Calcium hydroxide (1305-62-0)		
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	
Quartz (14808-60-7)		
Canada (Alberta) - Occupational Exposure Limits		
Local name	Silica-Crystalline: Quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate)	
Notations and remarks	Carcinogenicity A2	
Regulatory reference	Alberta Regulation 191/2021	
Canada (Quebec) - Occupational Exposure Limits	·	
Local name	Silica - Crystalline, Quartz	
VEMP (OEL TWAEV)	0.1 mg/m ³ (respirable dust)	
Notations and remarks	C2, EM	
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety	
Canada (British Columbia) - Occupational Exposure Limits		
Local name	Silica, Crystalline - alpha quartz	
OEL TWA	0.025 mg/m ³ (respirable)	
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)	
Canada (Manitoba) - Occupational Exposure Limits		
Local name	Silica crystaline - quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2023	
Canada (New Brunswick) - Occupational Exposure	Limits	
OEL TWA	0.025 mg/m ³ (respirable fraction)	
Canada (Newfoundland and Labrador) - Occupation	nal Exposure Limits	
Local name	Silica crystaline - quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2023	
Canada (Nova Scotia) - Occupational Exposure Lim	its	
Local name	Silica crystaline - quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2023	
L	1	

Safety Data Sheet

Quartz (14808-60-7)		
Canada (Nunavut) - Occupational Exposure Limits		
Local name	Silica - Crystalline: Quartz	
OEL TWA	0.05 mg/m³ (Trydimite removed-respirable fraction (Silica - crystalline)	
Notations and remarks	Designated substance	
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)	
Canada (Northwest Territories) - Occupational Expo	osure Limits	
Local name	Silica - Crystalline: Quartz	
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline)	
Notations and remarks	Designated substance	
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)	
Canada (Ontario) - Occupational Exposure Limits		
Local name	Silica, Crystalline - Quartz	
OEL TWA	0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline)	
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833	
Canada (Prince Edward Island) - Occupational Expo	osure Limits	
Local name	Silica crystaline - quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
Regulatory reference	ACGIH 2023	
Canada (Saskatchewan) - Occupational Exposure L	imits	
Local name	Silica - Crystalline: Quartz	
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed))	
Notations and remarks	Designated Chemical Substance	
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10	
Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	300 particle/mL (Silica - Quartz, crystalline)	
USA - ACGIH - Occupational Exposure Limits		
Local name	Silica crystaline - quartz	
ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
ACGIH chemical category	Suspected Human Carcinogen	
Regulatory reference	ACGIH 2023	
USA - OSHA - Occupational Exposure Limits	·	
Local name	Quartz (Total Dust) (Silica: Crystalline)	
OSHA PEL TWA [1]	50 μg/m³ (Respirable crystalline silica)	
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Quartz (14808-60-7)		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts	
8.2. Appropriate engineering controls		
Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.	
Environmental exposure controls	: Avoid release to the environment.	
8.3. Individual protection measures/Persona	I protective equipment	
Hand protection:		
Wear suitable gloves resistant to chemical penetration		
Eye protection:		
Wear eye/face protection		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respir hazards of the product and the safe working limits of	atory equipment. Respirator selection must be based on known or anticipated exposure levels, the the selected respirator.	

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties		
9.1. Information on basic phys	cal and chemical properties	
Physical state Colour	: Solid : Grayish White	

Coloui	
Odour	: Earthy
Odour threshold	: No data available
рН	: 12.45 at 25°C / 77 °F
Melting point	: 2570 – 2625 °C (4658 - 4757 °F)
Freezing point	: No data available
Boiling point	: 2850 °C / 5162 °F
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not applicable
Flammability	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density at 20 °C / 68 °F	: Not applicable
Relative density	: 2.4 – 3.6
Solubility	: Water: 0.1 - 0.125 g/100ml Solution at 20°C / 68 °F
Partition coefficient n-octanol/water	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive limits	: Not applicable
Explosive properties	: No data available
Oxidising properties	: No data available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with : Strong acids. Reacts with water to form Calcium Hydroxide. The heat generated when mixed with water or moist air is sufficient to ignite surrounding materials such as paper, wood or cloth.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Strong acids. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (dermal)	Not classified. Not classified. Not classified.	
Calcium carbonate (471-34-1)		
LD50 oral rat	6450 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
LC50 inhalation rat	 > 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) 	
ATE CA (oral)	6450 mg/kg bodyweight	
Carbonic acid, magnesium salt (1:1) (546-93-0))	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)	
Calcium oxide (1305-78-8)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))	

Safety Data Sheet

Calcium oxide (1305-78-8)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: other:US Federal Register 38: 187, Part 1500, Section 41, 1973.
LC50 inhalation rat	> 6.04 mg/l/4h
Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	3870 mg/kg
ATE CA (oral)	3870 mg/kg bodyweight
Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
LD50 dermal rat	> 2500 mg/kg
LC50 inhalation rat	> 6.04 mg/l/4h
ATE CA (oral)	7340 mg/kg bodyweight
Skin corrosion/irritation :	Causes skin irritation.
Serious eye damage/irritation :	pH: 12.45 at 25°C / 77 °F Causes serious eye damage. pH: 12.45 at 25°C / 77 °F
Respiratory or skin sensitisation : Germ cell mutagenicity : Operation of the sensitisation :	Not classified. Not classified.
	May cause cancer.
Quartz (14808-60-7) IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
	Yes
In OSHA Hazard Communication Carcinogen list Reproductive toxicity :	Not classified.
	May cause respiratory irritation.
Calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.
Calcium hydroxide (1305-62-0)	
STOT-single exposure	May cause respiratory irritation.
: STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Calcium oxide (1305-78-8)	
LOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Safety Data Sheet

Calcium oxide (1305-78-8)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.413 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified.
Dolomitic Lime Kiln Dust	
Viscosity, kinematic	Not applicable
Symptoms/effects after inhalation	May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Symptoms may include redness, drying, defatting and cracking of the skin. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general :	No known significant effects or critical hazards.	
Calcium oxide (1305-78-8)		
LC50 - Fish [1]	1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])	
EC50 - Crustacea [1]	49.1 mg/l Test organisms (species): Daphnia magna	
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosa Duration: '14 d'	
NOEC chronic fish	100 mg/l Test organisms (species): other:Tilapia nilotica Duration: '46 d'	
12.2. Persistence and degradability		
Dolomitic Lime Kiln Dust		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
Dolomitic Lime Kiln Dust		
Partition coefficient n-octanol/water	Not applicable	
Bioaccumulative potential	Not established.	
Calcium carbonate (471-34-1)		
BCF - Fish [1]	(no bioaccumulation)	
Calcium oxide (1305-78-8)		
BCF - Fish [1]	(no bioaccumulation)	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Calcium hydroxide (1305-62-0)	
BCF - Fish [1]	(no bioaccumulation)
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other information :	No other effects known.

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information	
-----------------------------------	--

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	 Not applicable Not applicable Not applicable 1910
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Not applicable Not applicable Not applicable Calcium oxide
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT)	: Not applicable
TDG Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG)	: Not applicable
IATA Transport hazard class(es) (IATA) Danger labels (IATA)	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	 Not applicable Not applicable Not applicable III
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
DOT No data available	
TDG No data available	
IMDG No data available	
IATA No data available	

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

WARNING: This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Carbonic acid, magnesium salt (1:1)(546-93-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List
Calcium oxide(1305-78-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Component	State or local regulations
Magnesium oxide (MgO)(1309-48-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Calcium hydroxide(1305-62-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Revision date : 2023-11-20

Revision date	:	202
Other information	:	No
Prepared by	:	Ne

- None.
- Nexreg Compliance Inc.



Full text of H-statements	
Carc. 1A Carcinogenicity, Category 1A	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Indication of changes:

Handling & storage

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.