

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Issue date: 12/16/2022 Revision date: 12/16/2022 Version: 1.0

SECTION 1: Identification		
1.1. Identification		
Product form Product name Product type Other means of identification	: Mixture : Granulime : Solid : Granulime, Lir	mestone, Calcium Carbonate, Calcite.
1.2. Recommended use and restrictions	on use	
Use of the substance/mixture	: Mineral filler, a	animal feed ingredient, pesticide carrier.
1.3. Supplier		
Manufacturer GRAYMONT #200-10991 Shellbridge Way Richmond, BC V6X 3C6 - Canada T 1 604 207-4292; Toll free1 866 207-4292 - F 1 www.graymont.com	604 207-9014	Distributor Graymont Western US Inc 585 W Southridge Way Sandy, Utah 84070 - United States T +1 801-262-3942
1.4. Emergency telephone number		
Emergency number		1 (800) 424-9300 International +1 (703) 527-3887 24 hr
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance or mixture		
GHS classification Carcinogenicity Category 1A Specific target organ toxicity – Repeated expose	ure, Category 1	
2.2. GHS Label elements, including precautionary statements		

GHS labelling

Hazard pictograms (GHS)

Signal word (GHS) Hazard statements (GHS)

Precautionary statements (GHS)



- : Danger
- : May cause cancer (Inhalation).
- Causes damage to organs (lungs) through prolonged or repeated exposure. : Obtain special instructions before use.
- Do not handle until all safety precations have been read and understood.
- Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling.
- wash hands, forearms and face thoroughly after hand
- Do not eat, drink or smoke when using this product
- Wear protective gloves/protective clothing/eye protection/face protection.
- If exposed or concerned: Get medical advice/attention.
- Store locked up.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Limestone	Limestone Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4-methyl-2-propyl-2H- tetrahydropyran-4-yl / Ground limestone	CAS-No.: 1317-65-3	90 – 100
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alphaQuartz / Silica, crystalline, .alphaquartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline- .alpha.quartz / Silica, .alphaquartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.0001 – 1

Comments

: Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.	
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.	
First-aid measures after skin contact	 If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists. 	
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.	
4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.	
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.	
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.	
4.3. Immediate medical attention and special treatment, if necessary		

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishing media			
Suitable extinguishing media Unsuitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.: Do not use water jet.		
5.2. Specific hazards arising from the chemical			
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Metal oxides.		
5.3. Special protective equipment and precautions for fire-fighters			
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).		

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective e	6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.		
6.1.1. For non-emergency personnel No additional information available			
6.1.2. For emergency responders No additional information available			
6.2. Environmental precautions			
Prevent entry to sewers and public waters.			
6.3. Methods and material for containment and cleaning up			
For containment Methods for cleaning up	 Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Provide ventilation. 		
6.4. Reference to other sections			

For further information refer to section 8: "Exposure controls/personal protection".

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Precautions for safe handling Hygiene measures	 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Good housekeeping is important to prevent accumulation of dust. Wear appropriate PPE (see Section 8). Wash contaminated clothing before reuse. Always wash hands after handling the product. 		
7.2. Conditions for safe storage, includ			
Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well- ventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Granulime		
No additional information available		
Limestone (1317-65-3)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³	
Canada (British Columbia) - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (total dust) 3 mg/m³ (respirable fraction)	
OEL STEL	20 mg/m³ (total)	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWA)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)	
Canada (Saskatchewan) - Occupational Exposure Limits		
OEL TWA	10 mg/m ³	
OEL STEL	20 mg/m ³	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
Quartz (14808-60-7)		
Canada (Alberta) - Occupational Exposure Limits		
Local name	Silica-Crystalline: Quartz	
OEL TWA	0.025 mg/m ³ (respirable particulate)	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Quartz (14808-60-7)		
Notations and remarks	Carcinogenicity A2	
Regulatory reference	Alberta Regulation 191/2021	
Canada (British Columbia) - Occupational Exposure Limits		
Local name	Silica, Crystalline - alpha quartz	
OEL TWA	0.025 mg/m³ (respirable)	
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)	
Canada (Ontario) - Occupational Exposure Limit	ts	
OEL TWA	0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline)	
Canada (Quebec) - Occupational Exposure Limi	ts	
VEMP (OEL TWA)	0.1 mg/m ³ (respirable dust)	
Canada (Saskatchewan) - Occupational Exposu	re Limits	
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed))	
USA - ACGIH - Occupational Exposure Limits		
Local name	Silica crystaline - quartz	
ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)	
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
ACGIH chemical category	Suspected Human Carcinogen	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limits		
Local name	Quartz (Total Dust) (Silica: Crystalline)	
OSHA PEL TWA [1]	50 μg/m³ (Respirable crystalline silica)	
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts	
USA - IDLH - Occupational Exposure Limits		
IDLH	50 mg/m ³ (respirable dust)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	0.05 mg/m ³ (respirable dust)	
USA - MSHA - Occupational Exposure Limits		
MSHA PEL TWA 8/40 h	30 mg/m ³ / (%SiO2) + 2 mg/m ³ (Total dust) 10 mg/m ³ / (%SiO2) + 2 mg/m ³ (Respirable dust)	
8.2. Appropriate engineering controls		
Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and	
Environmental exposure controls	safety showers. : Avoid release to the environment.	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state :	Solid	
Appearance :	Granules.	
Colour :	Dark brown; dark grey	
Odour :	Odourless	
Odour threshold :	No data available	
pH :	8 – 9.2 at 25°C (77 °F)	
Melting point :	No data available	
Freezing point :	No data available	
Boiling point :	No data available	
Flash point :	Not applicable	
Relative evaporation rate (butylacetate=1) :	Not applicable	
Flammability :	Not applicable	
Vapour pressure :	Not applicable	
Relative vapour density at 20°C / 68 °F:Relative density:	Not applicable 2.68 – 2.76	
Density :	2.68 – 2.76 g/cm ³	
Solubility :	Water: 6.6 mg/kg at 20°C (68 °F)	
Partition coefficient n-octanol/water :	Not applicable	
Auto-ignition temperature :	Not applicable	
Decomposition temperature :	870 °C (1598 °F)	
Viscosity, kinematic :	Not applicable	
Viscosity, dynamic :	No data available	
Explosive limits :	Not applicable	
Explosive properties :	No data available	
Oxidising properties :	No data available	

9.2. Other information

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reactivity

10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	Not classified.
Acute toxicity (dermal)	Not classified.
Acute toxicity (inhalation)	Not classified.
Skin corrosion/irritation	Not classified.
Serious eye damage/irritation	pH: 8 – 9.2 at 25°C (77 °F) Not classified.
ochous cyc danage/imaion	pH: 8 – 9.2 at 25°C (77 °F)
Respiratory or skin sensitisation	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	May cause cancer if inhaled. Risk of cancer depends on duration and level of exposure.
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	Not classified.
STOT-single exposure	Not classified.
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified.
Granulime	
Viscosity, kinematic	Not applicable
Symptoms/effects after inhalation	May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after eye contact		May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	:	May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms Other information		May cause cancer. Causes damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: No known significant effects or critical hazards.
12.2. Persistence and degradability	
Granulime	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Granulime	
Partition coefficient n-octanol/water	Not applicable
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	

Other information

: No other effects known.

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name		
Proper Shipping Name (DOT)	: Not applicable	
Proper Shipping Name (TDG)	: Not applicable	
Proper Shipping Name (IMDG)	: Not applicable	
Proper Shipping Name (IATA)	: Not applicable	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

()	
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT)	: Not applicable
TDG Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG)	: Not applicable
IATA Transport hazard class(es) (IATA)	: Not applicable
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	 Not applicable Not applicable Not applicable Not applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
DOT No data available	
TDG No data available	
IMDG No data available	
IATA No data available	
14.7. Transport in bulk according to An	nex II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory informatic	on

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

15.3. US State regulations

WARNING:

This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Limestone(1317-65-3)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

SECTION 16: Other information	
According to the Hazard Communication Stand Revision date Other information Prepared by	 lard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 : 12/16/2022 : None. : Nexreg Compliance Inc. www.Nexreg.com

Full text of H-statements	
Carc. 1A Carcinogenicity, Category 1A	
STOT RE 1 Specific target organ toxicity – Repeated exposure, Category 1	

SDS HazCom 2012 - WHMIS 2015 (Nexreg) - Section 15 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.